

What is claimed is:

1. An objective lens for converging a beam emitted by a light source on a recording surface of an optical disc, having compatibility with at least two types of optical discs of different data densities by employing diffracting structure having annular zones formed on at least one surface of the objective lens,

the surface on which the diffracting structure is formed including:

an inner area which focuses the beam on the recording surface of each optical disc substantially with no aberration both when a first beam of a first wavelength for information recording/readout of a first optical disc is incident thereon and when a second beam of a second wavelength for information recording/readout of a second optical disc having data density higher than that of the first optical disc is incident thereon; and

an outer area which focuses the second beam on the recording surface of the second optical disc substantially with no aberration while forming a wavefront that is substantially continuous with a wavefront of part of the second beam that passed through the inner area,

wherein the outer area includes at least one special annular zone which is formed so that part of the first beam that passed through the special annular zone will be substantially in phase with part of the first beam that passed through the inner area,

and

wherein a convergence angle θ [deg] of part of the first beam incident on the outermost part of the inner area measured after emerging from the objective lens and a design numerical aperture NA_{ref} as an NA (Numerical Aperture) necessary for the information recording/readout of the first optical disc satisfy:

$$0.9 < \sin\theta/NA_{ref} < 1.0, \text{ and}$$

wherein an effective NA of the objective lens for the first beam is set substantially equal to the numerical aperture NA_{ref} .

2. The objective lens according to claim 1, wherein phase difference ϕ [deg] between the phase of the part of the first beam that passed through the special annular zone and the phase of the part of the first beam that passed through the inner area satisfies:

$$-90^\circ < \phi < +90^\circ.$$

3. The objective lens according to claim 2, wherein the phase difference ϕ further satisfies:

$$-60^\circ \leq \phi \leq +60^\circ.$$

4. The objective lens according to claim 1, wherein a diameter W_1 of a beam spot formed on the recording surface of the first optical disc by the first beam that passed through the objective lens and a beam spot diameter W_{ref} obtained when an objective lens having an NA equal to the design numerical aperture NA_{ref} is used

satisfy:

$$0.99 < W1/W_{\text{ref}} < 1.01.$$

5. The objective lens according to claim 1, wherein at least one of the special annular zones satisfies the following condition regarding heights h_{min} and h_{max} of innermost and outermost parts of the special annular zone measured from the optical axis of the objective lens and height H of the outermost part of the inner area measured from the optical axis:

$$1.1 < (h_{\text{min}} + h_{\text{max}})/2H < 1.25.$$

6. The objective lens according to claim 1, wherein the design numerical aperture NA_{ref} for the first optical disc is 0.50 or more.

7. The objective lens according to claim 1, wherein an NA necessary for the information recording/readout of the second optical disc is 0.62 or more.

8. An objective lens for converging a beam emitted by a light source on a recording surface of an optical disc, having compatibility with at least two types of optical discs of different data densities by employing diffracting structure having annular zones formed on at least one surface of the objective lens,

the surface on which the diffracting structure is formed including:

an inner area which focuses the beam on the recording surface of each optical disc substantially with no aberration both when a first beam of a first wavelength suitable for information recording/readout of a first optical disc is incident thereon and when a second beam of a second wavelength suitable for information recording/readout of a second optical disc having data density relatively higher than that of the first optical disc is incident thereon; and

an outer area which focuses the second beam on the recording surface of the second optical disc substantially with no aberration while forming a wavefront that is substantially continuous with a wavefront of part of the second beam that passed through the inner area,

wherein the objective lens is placed so that the first beam will be incident thereon as a parallel beam,

wherein the outer area includes at least one special annular zone which is formed so that part of the first beam that passed through the special annular zone will be substantially in phase with part of the first beam that passed through the inner area,

wherein focal length f_1 of the objective lens for the first wavelength, height H of the outermost part of the inner area measured from the optical axis of the objective lens, and a design numerical aperture NA_{ref} as an NA (Numerical Aperture) necessary for the information recording/readout of the first optical disc satisfy:

$$0.9 < H/(f_1 \cdot NA_{ref}) < 1.0, \text{ and}$$

wherein an effective NA of the objective lens for the first beam is set substantially equal to the design numerical aperture NA_{ref} .

9. The objective lens according to claim 8, wherein phase difference ϕ [deg] between the phase of the part of the first beam that passed through the special annular zone and the phase of the part of the first beam that passed through the inner area satisfies:

$$-90^\circ < \phi < +90^\circ.$$

10. The objective lens according to claim 9, wherein the phase difference ϕ further satisfies:

$$-60^\circ \leq \phi \leq +60^\circ.$$

11. The objective lens according to claim 8, wherein a diameter W_1 of a beam spot formed on the recording surface of the first optical disc by the first beam that passed through the objective lens and a beam spot diameter W_{ref} obtained when an objective lens having an NA equal to the design numerical aperture NA_{ref} is used satisfy:

$$0.99 < W_1/W_{ref} < 1.01.$$

12. The objective lens according to claim 8, wherein at least one of the special annular zones satisfies the following condition regarding heights h_{min} and h_{max} of innermost and outermost parts

of the special annular zone measured from the optical axis of the objective lens:

$$1.1 < (h_{\min} + h_{\max})/2H < 1.25.$$

13. The objective lens according to claim 8, wherein the design numerical aperture NA_{ref} for the first optical disc is 0.50 or more.

14. The objective lens according to claim 8, wherein an NA necessary for the information recording/readout of the second optical disc is 0.62 or more.